## **PD10/15 SERIES POST HOLE DIGGERS**







## Two sizes: perfect for DIY!

The PD10 and PD15 Series Post Hole Diggers are just right for 3-Point attachment to Cat. 1 subcompact and compact utility tractors. These units offer a 30" or 48" auger length and a choice of 6", 9", & 12" auger flights with cast steel fishtail tips for quick piloting and faster hole starting. Landscapers, rental yards, contractors, farmers, ranchers, and land owners will find that the PD10 or the PD15 meets their general duty needs and applications.

Manhandling a Post Hole Digger by yourself is next to impossible. With our innovative Post Hole Digger storage stand, one person hook and unhook becomes a reality!



6", 9", 12", 15" & 18" Rock Augers available for PD15. (Tips highlighted for illustration)

Cast steel teeth are
replaceable, and positioned
for maximum digging
performance.

	PD10	PD15
Horsepower	15-30 HP	20-40 HP
Hitch	Cat. 1	
Yoke (cm)	2-7/8" (7.30) Tubing	
Boom (cm)	2-7/8" (7.30) Tubing	
Output Shaft (cm)	2" (5.08)	
Input RPM	540 Tractor at 300 RPM	
Driveline	Category 2	
<b>Component Protection</b>	Shear-Bolt Shear-Bolt	
Max Auger RPM	96	94
Auger Length	30"	48"
Dirt Auger Sizes	6", 9" or 12"	
Rock Auger Sizes	N/A	6", 9", 12", 15", 18"
Flighting Thickness	1/4"	
Options	Hydraulic Cylinder Down Pressure Kit (Applies approx. 500 lbs. of Force)*, Auger Extensions, Auger Alignment Handle, Storage Stand	

\*May not work in some cab applications.





## PD25/35 SERIES **POST HOLE DIGGERS**









## Additional power for those tougher jobs.

Land Pride PD25 and PD35 Series Post Hole Diggers are a good fit for heavy-duty applications. Landscapers, contractors, ranchers, and other land owners will appreciate the rugged dependability and the quality construction – these PDs will take a beating and last for years. Both are designed for Category 1 or 2 three-point attachment, offer a 48" auger length, and a choice of 6", 9", 12", 15", 18" or 24" auger flights with cast steel fishtail tips.



6", 9", 12", 15" & 18" Rock Augers available. (Tips highlighted for illustration)



Cast steel teeth are replaceable, and positioned for maximum digging performance.



	PD25	PD35
Horsepower	25-55 HP	30-75 HP
Hitch	2-7/8" (7.30) Tubing 3-1/2" (8.89) Reinforced Tubing	
Yoke (cm)		
Boom (cm)		
Output Shaft (cm)		
Input RPM	540 Tractor a	at 300 RPM
Driveline	Category 3	
<b>Component Protection</b>	Shear-Pin or	Radial Pin^
Max Auger RPM	48" 6", 9", 12", 15", 18" or 24"	
Auger Length		
Auger Sizes^		
Flighting Thickness		
Options	7" or 14" Auge Hydraulic Cylinder Kit^^ (Applies of of Force), Auger A Storage	r Down Pressure approx. 500 lbs. lignment Handle,

<sup>^</sup>Radial Pin recommended on auger sizes of 15" and above.

<sup>^^</sup>May not work in some cab applications.



