

# COMPACT TELEHANDLER

## TF27.6

**\$2,000** CREDIT  
ATTACHMENT OFFER

Allclass is now your authorised Merlo dealer – bringing you industry leading telehandlers built for tight worksites, high productivity, and premium operator comfort.

The **Merlo TF27.6** delivers:

- 2.7-tonne lift capacity
- 6-metre lift height
- Compact footprint for tight access
- Exceptional visibility and manoeuvrability
- Comfortable, high-spec Merlo cab

**BUY THE TF27.6 TILL THE END OF DECEMBER 2025 AND RECEIVE A \$2,000 CREDIT TOWARDS ANY MERLO ATTACHMENT.**

Perfect for maximising versatility across construction, agriculture, landscaping and material handling.

**UNLOCK PERFORMANCE, VERSATILITY AND VALUE – ALL IN ONE MACHINE.**

Contact **Allclass** today to secure your TF27.6 and claim your \$2,000 attachment credit.

1300 255 252 | [allclass.com.au](https://allclass.com.au)

  
**ALLCLASS**  
Est. 1992

 **MERLO**



| PERFORMANCE AND FEATURES                 | TF27.6                      |
|------------------------------------------|-----------------------------|
| <b>Performance</b>                       |                             |
| Unladen weight (kg)                      | 4850                        |
| Maximum load capacity (kg)               | 2700                        |
| Lift height (m)                          | 5.9                         |
| Maximum reach (m)                        | 3.3                         |
| Lift height at max. load capacity (m)    | 4.2                         |
| Reach at max. load capacity (m)          | 1.2                         |
| Load capacity at max. lift height (kg)   | 1500                        |
| Load capacity at max. reach (kg)         | 900                         |
| Boom section                             | 2                           |
| <b>Powertrain</b>                        |                             |
| Engine                                   | KOHLER 2504 TCR             |
| Range/Cylinders (l)                      | 2.5/4                       |
| Engine power (kW/HP)                     | 55.4/75.1                   |
| Anti-pollution technology                | Stage V - DOC + DPF         |
| Reversible Fan                           | —                           |
| Maximum speed (km/h)                     | 40                          |
| Fuel tank capacity (l)                   | 70                          |
| Hydrostatic transmission                 | TOP - 1V                    |
| EPD                                      | PLUS                        |
| Electronic joystick                      | —                           |
| Axles                                    | Axial                       |
| Reducers                                 | Epicyclic                   |
| Brakes                                   | Dry discs                   |
| Automatic parking brake                  | ●                           |
| <b>Hydraulic</b>                         |                             |
| Hydraulic pump                           | G + FS                      |
| Delivery / pressure (bar-l/min)          | 95-210                      |
| Hydraulic oil tank capacity (l)          | 70                          |
| Auxiliary hydraulic service on boom      | ●                           |
| Rear service line                        | ○                           |
| <b>Cab</b>                               |                             |
| Cab finishing                            | Standard                    |
| ASCS                                     | Light                       |
| FOPS II Cab                              | ●                           |
| ROPS Cab                                 | ●                           |
| Controls                                 | Electronic joystick control |
| Tilting cab                              | —                           |
| Reverse shuttle                          | Dual reverse                |
| <b>Configuration</b>                     |                             |
| Hydropneumatic Suspension CS Merlo       | —                           |
| Hydropneumatic Suspension BSS Merlo      | ○                           |
| Hydropneumatic Suspension EAS Merlo      | —                           |
| Work lights on cab                       | ●                           |
| Sun-shade in the cab                     | ○                           |
| Tac-lock                                 | ●                           |
| Pre-arrangement for aerial work platform | ○                           |
| Two floating forks                       | ●                           |
| Pedal Inching-Control                    | ●                           |
| Permanent four-wheel drive               | ●                           |
| All wheel steering                       | ●                           |
| Three steering way                       | ●                           |
| Standard tyres                           | 12/75-18"                   |
| OPT tyres                                | 300/80-15.3"                |
| Hydraulically controlled stabilizers     | —                           |
| Tractor type approval                    | —                           |
| Pneumatic brakes (ton)                   | —                           |
| Hydraulic brakes (ton)                   | ○                           |

KEY: — not available ● standard ○ optional



| DIMENSIONS                   | TF27.6 |
|------------------------------|--------|
| A - Length                   | 3910   |
| C - Wheelbase                | 2450   |
| F - Ground clearance         | 330    |
| H - Width                    | 1860   |
| M - Cabin width              | 1010   |
| P - Height                   | 2020   |
| R - Turning radius at wheels | 3370   |
| S - Turning radius at forks  | 4200   |

